


TERMINAIS DE COMPRESSÃO DE COBRE ESTANHADO



- 1 furo
- 1 compressão
- Tensão máxima: 35 kV



CÓDIGO	SEÇÃO DO CONDUTOR	DIMENSÕES				EMBALAGEM		
		L	H	d	D	PACOTE	MID.	MASTER
TCC11001	1,5 mm ²	16 mm	6,5 mm	5,2 mm	8,0 mm	100 un	30 pct.	120 pct.
TCC11002	2,5 mm ²	20,2 mm	6,4 mm	5,3 mm	7,7 mm	100 un	10 pct.	160 pct.
TCC11004	4,0 mm ²	20 mm	7,5 mm	5,2 mm	10,0 mm	100 un	10 pct.	130 pct.
TCC11006	6,0 mm ²	23 mm	8,0 mm	5,2 mm	10,0 mm	100 un	10 pct.	120 pct.
TCC11010	10,0 mm ²	25 mm	9,0 mm	6,5 mm	12,0 mm	100 un	5 pct.	80 pct.
TCC11016	16,0 mm ²	30 mm	11,0 mm	6,5 mm	12,0 mm	50 un	10 pct.	100 pct.
TCC11025	25,0 mm ²	33 mm	13,5 mm	6,5 mm	13,0 mm	50 un	8 pct.	72 pct.
TCC11035	35,0 mm ²	38 mm	14,5 mm	8,4 mm	15,3 mm	50 un	4 pct.	48 pct.
TCC11050	50,0 mm ²	45 mm	17,0 mm	10,5 mm	17,8 mm	50 un	2 pct.	28 pct.
TCC11070	70,0 mm ²	50 mm	19,5 mm	10,5 mm	21,0 mm	50 un	-	16 pct.
TCC11095	95,0 mm ²	55 mm	23,5 mm	10,5 mm	25,0 mm	10 un	-	60 pct.
TCC11120	120,0 mm ²	63 mm	26,0 mm	13,0 mm	28,0 mm	10 un	-	42 pct.
TCC11150	150,0 mm ²	70 mm	29,0 mm	17,0 mm	30,0 mm	10 un	-	40 pct.
TCC11185	185,0 mm ²	75 mm	33,0 mm	17,0 mm	34,0 mm	10 un	-	24 pct.
TCC11240	240,0 mm ²	90 mm	40,0 mm	21,0 mm	38,0 mm	10 un	-	18 pct.
TCC11300	300,0 mm ²	98 mm	44,0 mm	21,0 mm	43,0 mm	10 un	-	12 pct.