



CÓDIGO	SEÇÃO DO CONDUTOR	DIMENSÕES				COR	TENSÃO MÁXIMA	EMBALAGEM		
		L	H	d	D			PACOTE	MID.	MASTER
TPA10103	0,5 - 1,5 mm <sup>2</sup>	21,5 mm	11,5 mm	3,7 mm	8,0 mm	VERMELHA	450 V	100 un	10 pct.	240 pct.
TPA10104	0,5 - 1,5 mm <sup>2</sup>	21,5 mm	11,5 mm	4,3 mm	8,0 mm	VERMELHA	450 V	100 un	10 pct.	240 pct.
TPA10105	0,5 - 1,5 mm <sup>2</sup>	21,5 mm	11,5 mm	5,3 mm	8,0 mm	VERMELHA	450 V	100 un	10 pct.	240 pct.
TPA10106	0,5 - 1,5 mm <sup>2</sup>	27,5 mm	17,5 mm	6,5 mm	11,6 mm	VERMELHA	450 V	100 un	10 pct.	240 pct.
TPA10108	0,5 - 1,5 mm <sup>2</sup>	27,5 mm	17,5 mm	8,4 mm	11,6 mm	VERMELHA	450 V	100 un	10 pct.	240 pct.
TPA10203	1,5 - 2,5 mm <sup>2</sup>	22,5 mm	12,5 mm	3,7 mm	8,5 mm	AZUL	450 V	100 un	10 pct.	200 pct.
TPA10204	1,5 - 2,5 mm <sup>2</sup>	22,5 mm	12,5 mm	4,3 mm	8,5 mm	AZUL	450 V	100 un	10 pct.	200 pct.
TPA10205	1,5 - 2,5 mm <sup>2</sup>	22,5 mm	12,5 mm	5,3 mm	9,5 mm	AZUL	450 V	100 un	10 pct.	200 pct.
TPA10206	1,5 - 2,5 mm <sup>2</sup>	27,6 mm	17,6 mm	6,5 mm	12,0 mm	AZUL	450 V	100 un	10 pct.	200 pct.
TPA10208	1,5 - 2,5 mm <sup>2</sup>	27,6 mm	17,6 mm	8,4 mm	12,0 mm	AZUL	450 V	100 un	10 pct.	200 pct.
TPA10603	4,0 - 6,0 mm <sup>2</sup>	21,4 mm	8,9 mm	3,7 mm	7,2 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10604	4,0 - 6,0 mm <sup>2</sup>	25,5 mm	13,0 mm	4,3 mm	9,5 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10605	4,0 - 6,0 mm <sup>2</sup>	25,5 mm	13,0 mm	5,3 mm	9,5 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10606	4,0 - 6,0 mm <sup>2</sup>	31,5 mm	19,0 mm	6,5 mm	12,0 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10608	4,0 - 6,0 mm <sup>2</sup>	31,5 mm	21,2 mm	8,4 mm	15,0 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10610	4,0 - 6,0 mm <sup>2</sup>	33,7 mm	21,2 mm	10,5 mm	15,0 mm	AMARELA	450 V	100 un	10 pct.	100 pct.
TPA10613	4,0 - 6,0 mm <sup>2</sup>	37,3 mm	24,0 mm	13,0 mm	18,5 mm	AMARELA	450 V	100 un	10 pct.	80 pct.
TPA11004	10,0 mm <sup>2</sup>	30,0 mm	13,0 mm	4,3 mm	8,7 mm	VERMELHA	450 V	100 un	10 pct.	60 pct.
TPA11005	10,0 mm <sup>2</sup>	32,5 mm	15,0 mm	5,3 mm	8,8 mm	VERMELHA	450 V	100 un	10 pct.	60 pct.
TPA11006	10,0 mm <sup>2</sup>	31,9 mm	15,0 mm	6,5 mm	11,8 mm	VERMELHA	450 V	100 un	10 pct.	60 pct.
TPA11008	10,0 mm <sup>2</sup>	37,8 mm	21,0 mm	8,4 mm	14,8 mm	VERMELHA	450 V	100 un	10 pct.	60 pct.
TPA11010	10,0 mm <sup>2</sup>	37,8 mm	21,0 mm	10,5 mm	14,8 mm	VERMELHA	450 V	100 un	10 pct.	60 pct.
TPA11605	16,0 mm <sup>2</sup>	38,3 mm	18,5 mm	5,3 mm	12,0 mm	AZUL	450 V	50 un	10 pct.	60 pct.
TPA11606	16,0 mm <sup>2</sup>	38,3 mm	18,5 mm	6,5 mm	12,0 mm	AZUL	450 V	50 un	10 pct.	60 pct.
TPA11608	16,0 mm <sup>2</sup>	40,9 mm	21,0 mm	8,4 mm	16,0 mm	AZUL	450 V	50 un	10 pct.	60 pct.
TPA11610	16,0 mm <sup>2</sup>	40,9 mm	21,0 mm	10,5 mm	16,0 mm	AZUL	450 V	50 un	10 pct.	60 pct.
TPA12505	25,0 mm <sup>2</sup>	43,3 mm	21,0 mm	5,3 mm	12,0 mm	AMARELA	450 V	50 un	10 pct.	40 pct.
TPA12506	25,0 mm <sup>2</sup>	43,3 mm	21,5 mm	6,5 mm	16,6 mm	AMARELA	450 V	50 un	10 pct.	40 pct.
TPA12508	25,0 mm <sup>2</sup>	43,3 mm	21,5 mm	8,4 mm	16,6 mm	AMARELA	450 V	50 un	10 pct.	40 pct.
TPA12510	25,0 mm <sup>2</sup>	43,3 mm	21,5 mm	10,5 mm	16,6 mm	AMARELA	450 V	50 un	10 pct.	40 pct.
TPA13505	35,0 mm <sup>2</sup>	47,0 mm	24,5 mm	5,3 mm	15,0 mm	VERMELHA	450 V	50 un	10 pct.	20 pct.
TPA13506	35,0 mm <sup>2</sup>	48,0 mm	24,5 mm	6,5 mm	15,0 mm	VERMELHA	450 V	50 un	10 pct.	20 pct.
TPA13508	35,0 mm <sup>2</sup>	48,0 mm	24,5 mm	8,4 mm	15,0 mm	VERMELHA	450 V	50 un	10 pct.	20 pct.
TPA13510	35,0 mm <sup>2</sup>	48,0 mm	24,5 mm	10,5 mm	15,0 mm	VERMELHA	450 V	50 un	10 pct.	20 pct.
TPA13513	35,0 mm <sup>2</sup>	52,0 mm	28,0 mm	13,5 mm	22,0 mm	VERMELHA	450 V	50 un	10 pct.	20 pct.