


TERMINAIS PRÉ-ISOLADOS TIPO TUBO SIMPLES (ILHÓS)



CÓDIGO	SEÇÃO DO CONDUTOR	DIMENSÕES				COR	TENSÃO MÁXIMA	EMBALAGEM		
		L	H	d	D			PACOTE	MID.	MASTER
TPT0008	1 x 0,5 mm ²	14,0 mm	8,0 mm	1,0 mm	2,6 mm	BRANCA	450 V	50 un	10 pct.	2500 pct.
TPT00010	1 x 0,5 mm ²	16,0 mm	10,0 mm	1,0 mm	2,6 mm	BRANCA	450 V	50 un	10 pct.	2000 pct.
TPT10008	1 x 0,75 mm ²	14,6 mm	8,0 mm	1,3 mm	2,8 mm	CINZA	450 V	50 un	10 pct.	2000 pct.
TPT10012	1 x 0,75 mm ²	18,4 mm	12,0 mm	1,3 mm	2,8 mm	CINZA	450 V	50 un	10 pct.	2000 pct.
TPT10108	1 x 1,0 mm	14,6 mm	8,0 mm	1,5 mm	3,0 mm	VERMELHA	450 V	50 un	10 pct.	2000 pct.
TPT10112	1 x 1,0 mm	18,4 mm	12,0 mm	1,5 mm	3,0 mm	VERMELHA	450 V	50 un	10 pct.	1750 pct.
TPT10109	1 x 1,5 mm ²	14,6 mm	8,0 mm	1,8 mm	3,5 mm	PRETA	450 V	50 un	10 pct.	1600 pct.
TPT10110	1 x 1,5 mm ²	16,4 mm	10,0 mm	1,8 mm	3,5 mm	PRETA	450 V	50 un	10 pct.	1400 pct.
TPT10118	1 x 1,5 mm ²	24,4 mm	18,0 mm	1,8 mm	3,5 mm	PRETA	450 V	50 un	10 pct.	1000 pct.
TPT10208	1 x 2,5 mm ²	15,2 mm	8,0 mm	2,3 mm	4,0 mm	AZUL	450 V	50 un	10 pct.	1200 pct.
TPT10212	1 x 2,5 mm ²	19,2 mm	12,0 mm	2,3 mm	4,0 mm	AZUL	450 V	50 un	10 pct.	1200 pct.
TPT10218	1 x 2,5 mm ²	25,2 mm	18,0 mm	2,3 mm	4,0 mm	AZUL	450 V	50 un	10 pct.	1000 pct.
TPT10409	1 x 4,0 mm	16,5 mm	9,0 mm	2,8 mm	4,4 mm	CINZA	450 V	50 un	10 pct.	1000 pct.
TPT10412	1 x 4,0 mm	19,5 mm	12,0 mm	2,8 mm	4,4 mm	CINZA	450 V	50 un	10 pct.	900 pct.
TPT10418	1 x 4,0 mm	25,5 mm	18,0 mm	2,8 mm	4,4 mm	CINZA	450 V	50 un	10 pct.	750 pct.
TPT10612	1 x 6,0 mm ²	20,0 mm	12,0 mm	3,5 mm	6,3 mm	AMARELA	450 V	50 un	10 pct.	700 pct.
TPT10618	1 x 6,0 mm ²	26,0 mm	18,0 mm	3,5 mm	6,3 mm	AMARELA	450 V	50 un	10 pct.	600 pct.
TPT11012	1 x 10 mm ²	21,2 mm	11,8 mm	4,25 mm	7,0 mm	VERMELHA	450 V	50 un	10 pct.	500 pct.
TPT11018	1 x 10,0 mm ²	27,5 mm	18,0 mm	4,5 mm	7,6 mm	VERMELHA	450 V	50 un	10 pct.	400 pct.
TPT11022	1 x 10,0 mm ²	31,9 mm	22,0 mm	4,5 mm	7,6 mm	VERMELHA	450 V	50 un	10 pct.	320 pct.
TPT11025	1 x 10,0 mm ²	34,7 mm	25,0 mm	4,5 mm	7,6 mm	VERMELHA	450 V	50 un	10 pct.	320 pct.
TPT11618	1 x 16,0 mm ²	28,2 mm	18,0 mm	5,8 mm	8,8 mm	AZUL	450 V	50 un	10 pct.	300 pct.
TPT11622	1 x 16,0 mm ²	32,0 mm	22,0 mm	5,8 mm	8,7 mm	AZUL	450 V	50 un	10 pct.	260 pct.
TPT11625	1 x 16,0 mm ²	35,0 mm	25,0 mm	5,8 mm	8,7 mm	AZUL	450 V	50 un	10 pct.	260 pct.
TPT12516	1 x 25,0 mm ²	29,0 mm	16,0 mm	7,5 mm	11,2 mm	AMARELA	450 V	50 un	10 pct.	200 pct.
TPT12518	1 x 25,0 mm ²	30,0 mm	18,0 mm	7,5 mm	11,2 mm	AMARELA	450 V	50 un	10 pct.	200 pct.
TPT12522	1 x 25,0 mm ²	34,0 mm	22,0 mm	7,5 mm	11,2 mm	AMARELA	450 V	50 un	10 pct.	160 pct.
TPT13518	1 x 35,0 mm ²	30,0 mm	18,0 mm	8,3 mm	12,7 mm	VERMELHA	450 V	50 un	10 pct.	160 pct.
TPT13525	1 x 35,0 mm ²	39,0 mm	25,0 mm	8,3 mm	12,7 mm	VERMELHA	450 V	50 un	10 pct.	140 pct.
TPT15020	1 x 50,0 mm ²	36,0 mm	20,0 mm	10,3 mm	15,3 mm	AZUL	450 V	25 un	10 pct.	160 pct.
TPT15025	1 x 50,0 mm ²	41,0 mm	25,0 mm	10,3 mm	15,3 mm	AZUL	450 V	25 un	10 pct.	160 pct.
TPT17025	1 x 70,0 mm ²	37,0 mm	20,0 mm	13,5 mm	16,0 mm	AMARELA	450 V	25 un	10 pct.	100 pct.
TPT17020	1 x 70,0 mm ²	42,0 mm	25,0 mm	13,5 mm	16,0 mm	AMARELA	450 V	25 un	10 pct.	100 pct.
TPT19525	1 x 95,0 mm ²	43,7 mm	24,5 mm	14,1 mm	19,0 mm	VERMELHA	450 V	25 un	10 pct.	100 pct.
TPT112027	1 x 120 mm ²	47,5 mm	26,8 mm	16,2 mm	21,3 mm	AZUL	450 V	25 un	-	60 pct.
TPT112032	1 x 120 mm ²	52,6 mm	31,7 mm	16,3 mm	21,1 mm	AZUL	450 V	25 un	-	60 pct.
TPT115032	1 x 150 mm ²	57,2 mm	31,5 mm	19,3 mm	23,8 mm	AMARELA	450 V	25 un	-	50 pct.